



TRANSPARENT ADHESIVE CALENDERED VINYL

PRODUCT: SAV-120T

- Transparent Film
- indoor & outdoor signage and wide-format digital printing such as vehicle advertising, outdoor durable signage and product labels
- Matte & gloss surface available

MATERIAL DETAILS

WATERIAL DETAILS			
PROPERTIES	TEST METHOD	METRIC	
PVC Film			
Туре	1	Calendered monomeric soft PVC film	
Thickness	1	80micron/3mil	
Color	1	Clear	
Shrinking	1	≦0.8%	
Surface Tension	1	≧30dn/cm	
Surface Finishing	1	70-90%	
Adhisive			
Adhesive Type	1	Clear solvent based permanent pressure sensitive glue	
Weight(g/m2)	1	25±2	
Adhesion Temperature	1	15°C~40°C	
Peeling Force	GB2792-81China National Standard	≧6.5N/25mm 20min	
Initial Adhesion-Ball Tack	GB4852-84 China National Standard	≧5# Steel Ball	
Release Paper			
Туре	1	Kraft paper	
Thickness(mm)	1	180micron (0.18mm)	
Weight	1	120g//sq.m 3.5oz/sq.yd	
Color	1	White	
Release Force	1	0.05~0.2N/25mm	
Available Size	1	42"/50"/54"/60" 50m	

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye Sublimation Transfer	Dye Sublimation Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co	., Ltd
(Sovang Headquarter)	

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive Altham Industrial estate Altham Lancashire BB5 5TU UK.

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982