

3D CALENDERED COLD LAMINATION FILM

PRODUCT: 3DC-6004

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
Face Film		
Material	/	PP
Surface	/	Glossy
Pattern	/	Sparkling
Color	/	Clear
Thickness(mm)	/	0.07+/-0.01
Weight(gram/sqm)	/	65
Liner		
Material	/	coated paper
Thickness(mm)	/	0.18+/-0.01
Weight(gram/sqm)	/	120g/sq.m 3.5oz
Adhesive		
Type	/	Clear solvent based pressure sensitive glue (meet Rohs
Weight(gram/sqm)	/	22±2
Adhesion Temperature	/	15°C~40°C
Width available(m)	/	36"/42"/50"/54"/60" 50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye Sublimation Transfer	Dye Sublimation Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability.
The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf DriveAltham Industrial estateAltham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982