

TRANSPARENT PERFORATED WINDOWS FILM
PRODUCT: SUNSHADE IV-64

- Transparent film with clear solvent base removable glue.
- 60/40 perforated pattern
- For UV white ink printing and useable inside of the windows.

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
PVC		
Thickness	/	180micron/7mil
Color	/	Clear
Shrinkage	/	≤0.8%
Surface Tension	/	≥30dn/cm
Opacity	/	>99%
Holes No.	/	Average 130/sq in
Hole Diameter	/	1.6mm
Distance Between Holes	/	2.4mm
Hole Space	/	41%
Adhesive		
Type	/	Clear solvent based removable pressure sensitive glue
Weight(g/m ²)	/	30±2
Adhesion Temperature	/	15°C~40°C
Peeling Force	/	≥5N/25mm
Initial Adhesion- Ball Tack	GB4852-84	≥5# Steel Ball
Holding Power	GB4854-84	≥800min
Removable Durability	/	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
Liner		
Type	/	Laminaed OPP Film
Color	/	Clear
Weight	/	165g/sq.m 3oz/sq.yd
Release Force	/	0.4~1N/4cm
Available Size	/	36"/42"/50"/54"/60" 50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
☐	☐		
Screen Printing	Dye Sublimation Transfer	Dye Sublimation Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Technologies Co., Ltd
(Soyang Headquarter)**

West 19th FL, Yongtong Information plaza,
No. 141 Huancheng Bei Road, Hangzhou
City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf
DriveAltham Industrial
estateAltham Lancashire BB5 5TU
UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982