

TRANSPARENT LASER PERFORATED WINDOWFILM

PRODUCT: SUNSHADE LSV-64

- Clear film , with laser layer and white coating
- Indoor and Outdoor digital printing media for indoor decoration, signage display, vehicle graphics, airport and subway graphics application.
- 60/40 perforated pattern

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
Face Film		
Material	/	PVC
Color	/	clear film , with laser layer and white coating
Pattern	/	dot
Tthickness	/	140micron/5.5mil
Weight(gram/sqm)	/	230+/-15
Adhesive		
Type	/	Clear solvent based removable pressure sensitive glue (meet Rohs requirement)
Weight(g/m ²)	/	18±2
Adhesion Temperature	/	15°C~40°C
Removable Durability	/	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
Liner		
Type	/	Kraft paper
Thickness(mm)	/	0.16+/-0.01
Weight	/	140g/sq.m 4oz/sq.yd
Available Size	/	50"/50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
☐	☐		
Screen Printing	Dye Sublimation Transfer	Dye Sublimation Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd

(Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf DriveAltham Industrial estateAltham Lancashire B85 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982