

Glossy PP Film/Adhesive 120

PRODUCT: WP-120GL

MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC |
|----------------|-------------|-------------------------|
| Weight | / | / |
| Thickness | / | 120micron/4.7mil |
| Surface | / | Glossy |
| Available Size | / | 36"/42"/50"/54"/60"/30m |

INK PRINTABILITY

| Solvent | Eco Solvent | UV | Latex |
|-----------------|--------------------------|--------------------------|--------------------------|
| | | <input type="checkbox"/> | <input type="checkbox"/> |
| Screen Printing | Dye Sublimation Transfer | Dye Sublimation Direct | Water based |
| | | | <input type="checkbox"/> |

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Technologies Co., Ltd
(Soyang Headquarter)**

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK.

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982