


Non-woven + Embossed Latex Carpet

PRODUCT: DGF-011

FEATURES:

- 100% PES non-woven fabric on top surface and embossed latex layer on the backside
- Perfect anti-slip feature makes it an ideal carpet material
- Excellent performance on flexibility, unlikely to be distortion
- Moisture proof with very good ventilation capacity
- Compatible with heat transfer printing and Latex/UV inks



APPLICATIONS:

- Indoor deco carpet Foot pad Door mat

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	1150 g/sq.m.	33.9 oz/sq.yd.
Non-woven Fabric Weight	DIN EN ISO 2286-2, ASTM D751	350 g/sq.m.	/
Natural Latex Weight	DIN EN ISO 2286-2, ASTM D751	800 g/sq.m.	/
Raw Material	N/A	100% polyester + Natural latex	
Width (Type I)	DIN EN ISO 3759, ASTM D751-2006	Max320cm	126"
Width (Type II)	DIN EN ISO 3759, ASTM D751-2006	Max400cm	157"

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	
	<input type="checkbox"/>		

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

Soyang Technologies Co., Ltd

(Soyang Headquarters)

West 19th FL, Yongtong
Information plaza, No. 141
Huancheng Bei Road, Hangzhou

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co.,Ltd

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Hangzhou Soyang Flexible Material Co.,Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf
Drive
Altham Industrial estate

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982