

Satin Blockout Fabric



ST-218T/ST-218D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% knitted satin polyester fabric, glossy finish

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	400 g/sq.m	11.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted 2 bar	
Dry Heat Shrinkage	N/A	≤3% (210℃, 30s)	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Recommend Fixation Temperature	N/A	190℃-210℃, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥210℃	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 160cm	63"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.