

Prime Display Fabric Classic



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-117T/ST-117D

BRIEF DESCRIPTION

- 100% polyester warp knitted fabric with tight structure
- Wrinkle-resistant
- Can be used as display, pop up & backdrop material

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	220 g/sq.m	6.4oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	(56±4)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, NF P92 M1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, NF P92 M1, EN13501-1	
Recommend Fixation Temperature	N/A	190 °C-210 °C, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥210 °C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

