

SL-M02

Soyang's innovative eco range: PVC-Free. Degradable.
Oekotex Standard 100 Certificated.

BRIEF DESCRIPTION

- 1000Dx1000D 12x12/inch polyester mesh
- Max 197" width keeps it widely used in outdoor applications

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	150 g/sq.m	4.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	1100x1100 dtex	1000x1000 denier
Number of Threads Per Unit	GB/T 4668	/	12x12/inch
Tensile Strength	DIN EN ISO 1421	1714x1533 N/5cm	196x175lbs/inch
Tear Strength	DIN 53363	683x721N	154x162lbs
Flame Resistance	DIN 4102-1-B1	DIN 4102-1-B1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.