

Fur Guard
PRODUCT:IDFL1199E
FEATURES

- Fully matte leather-embossing finish on the surface, making it elegant and unique;
- High strength and excellent cleanability;
- Value fabric to satisfy your budget.

APPLICATIONS

Ideal for sofa/bed covers and general purpose covers, Gym divider curtains, tarpaulins, sports bags, etc.



SPECIFICATIONS		TEST METHOD
Composition	1100Dtex *1100Dtex 3.5*3.5/cm	DIN 53830/DIN60001
	1000D *1000D 9*9/inch	ASTM D 751
Weight	480 gsm +/- 20gsm	DIN53352
	14oz	ASTM D 751
Surface finish	Fully matte	
Color	Upon request	
Tensile Strength (Warp/Weft)	1395/1100 N/5cm	DIN 53354
	317/250 lbs/2"	FS 5100
Tear Strength (Warp/Weft)	330/270N	DIN 53363
	75/61lbs	FS 5100
Adhesion Strength	/	DIN 53357
		FS 5970
Width	1000 ~ 2500mm	
	36" ~ 98"	
Fire Resistance	B1	
Temperature Resistance	- 20°C ~ 70°C	DIN 53372
	- 4°F ~ 158°F	FS 5874

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Technologies Co., Ltd
(Soyang Headquarters)**

West 19th FL, Yongtong Information plaza,
No. 141 Huancheng Bei Road, Hangzhou
City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982