

Lightweight Coated Fabric 11oz/375gsm

PRODUCT: IDFK333636

FEATURES

- High tensile and tear strength, and good welding ability;
- Excellent ability on anti-UV, fire-retardant and self-cleaning;
- Good anti-abrasion ability;
- Super light on weight and highly smooth on surface.

APPLICATIONS

- Ideal for industrial applications, like ventilation ducting, industrial apron, etc.



SPECIFICATIONS		
Composition	330Dtex*330Dtex 14*14/cm	DIN 53830/DIN60001
	300D*300D 36*36/inch	ASTM D 751
Weight	375gsm	DIN53352
	11oz	ASTM D 751
Lacquering	1/1 Acrilic (upon request)	
Surface finish	Glossy or Matte	
Color	upon request	
Breaking Strength(Warp x Weft)	1400/1300 N/5cm	DIN 53354
	318/295 lbs/2"	FS 5100
Tearing Strength (Warp x Weft)	160/140 N/5cm	DIN 53363
	36/32 lbs/2"	FS 5100
Adhesion Strength	60 N/5cm	DIN 53357
	13.5 lbs/2"	FS 5970
Width	1000~3200 mm	
	36"~126"	
Fire Resistance	B1, B2, NF-PA701	
Temperature Resistance	-30°C ~ 70°C	DIN 53372
	-20°F ~ 158°F	FS 5874

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982