

SOLAR SCREEN

PRODUCT: SS-9222

FEATURES

- Exceptional rolling space, strong dimensional ability and excellent tensile strength;
- Good heat and sunlight protection features;
- Superior weather resistance providing a long-term durability;
- The evenly-woven structure guarantees optimal visual comfort and gives off a harmonious light.

APPLICATIONS

- Indoor and outdoor applications, like window blinds, garden shades, skylight blinds, panel shades, etc.



SPECIFICATIONS	
Composition	25% Polyester, 75% PVC 36*36(2*2)
Weight	510gsm
Thickness	0.75mm
Openness Factor	8%
Tensile Strength(daN/5cm)	1100N/1000N
Tearing Strength (daN)	20N/20N
Width	1830/2500/3000 mm
Fire Resistance	B1
Color Fastness	8

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982