

Silver-Backing Laminated Tent Fabric

PRODUCT: TFL25251921

FEATURES

- Silver color on the back side makes dirt less visible but more elegant-looking of the fabric.
- Good light-stop performance thanks to its silver back.
- Best value to meet your budget.

APPLICATIONS

- Ideal for short-term mobile fabric structures



SPECIFICATIONS		
Composition	278Dtex *278Dtex 7.5*8.2 /cm	DIN 53830/DIN60001
	250D*250D 19*21/inch	ASTM D 751
Weight	445 gsm	DIN53352
	13 oz	ASTM D 751
Surface finish	Glossy	
Color	White/Silver Back	
Tensile Strength (Warp x Weft)	968x817 N/5cm	DIN 53354
	220X185 lbs/2"	FS 5100
Tearing Strength (Warp x Weft)	160x158N	DIN 53363
	36X35 lbs	FS 5100
Adhesion Strength	40N/5cm	DIN 53357
	9lbs/2"	FS 5970
Width	155mm	
	61"	
Fire Resistance	B1, B2, NFPA-701	
Temperature Resistance	- 30°C ~ 70°C	DIN 53372
	- 20°F ~ 158°F	FS 5874

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarters)

West 19th FL, Yongtong
Information plaza, No. 141
Huancheng Bei Road, Hangzhou
City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982