

**SOLAR SCREEN**
**PRODUCT: SS-9522**
**FEATURES**

- Exceptional rolling space, strong dimensional ability and excellent tensile strength;
- Good heat and sunlight protection features;
- Superior weather resistance providing a long-term durability;
- The evenly-woven structure guarantees optimal visual comfort and gives off a harmonious light.

**APPLICATIONS**

- Indoor and outdoor applications, like window blinds, garden shades, skylight blinds, panel shades, etc.



SPECIFICATIONS	
Composition	30% Polyester, 70% PVC 48*48(2*2)
Weight	400gsm
Thickness	0.55mm
Openness Factor	5%
Tensile Strength(daN/5cm)	1300N/1200N
Tearing Strength (daN)	20N/20N
Width	1830/2500/3000/3200 mm
Fire Resistance	B1
Color Fastness	8

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Technologies Co., Ltd  
(Soyang Headquarters)**

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

[www.soyang.net](http://www.soyang.net)

P. 0086-571-28918690

F. 0086-571-28918695

**Soyang Haining Factory**

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

**Soyang Hangzhou Factory**

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

**Soyang Europe Ltd**

Calder House Metcalf Drive  
Altham Industrial estate  
Altham Lancashire BB5 5TU UK

[www.soyang.co.uk](http://www.soyang.co.uk)

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982