



600D PU Coated SD Polyester Fabric

PRODUCT: 600D SD Polyester

FEATURES

- Outstanding colorfastness
- Excellent ability on waterproof
- Good anti-abrasion ability

APPLICATIONS

- Ideal for various industrial applications, like boat covers, umbrellas and etc.

SPECIFICATIONS	TEST METHOD		
Composition	600D 100% Solution dye polyester		
Weight	260gsm +/- 20gsm		DIN53352
	7.6oz +/- 0.6oz		ASTM D3776
Color	upon specific request		
Width	1000~3200mm		
Coating	0/1 PU coating		
Hydrostat	≥1000mm		AATCC 127
Water repellency	≥90		AATCC 22
Mildew	99.90	0%	AATCC 30 Part III
Tensile strength	≥ 1554N/350lbs (Warp)	≥ 1110N/250lbs (Weft)	ASTM D5034
Tear strength	≥ 64Nm (Warp)	≥ 64Nm (Weft)	ASTM D1424 Falling-Pendulum (Elmendorf-Type)
UV Colorfastness	≥4.5, fabric face		AATCC 16E, Option 3, 720h
	≥4, PU coated face		AATCC 16E, Option 3, 720h
Heat shrinkage	≤2% warp, ≤2% weft		

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)	Soyang Haning Factory	Soyang Hangzhou Facotory	Soyang Europe Ltd
West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.	No. 36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR., China	No. 1199, Gongyuan Xi Road, Fuyang, Hangzhou City, Zhejiang PR., China	Calder House Metcalf Drive, Altham Accrington, Lancashire BB5 5TU UK
www.soyang.net			www.soyang.co.uk
P. 0086-571-28918697			P. 0044-161 765 3400
F. 0086-571-28918695			F. 0044-1282 772 982