

600D Solution Dye Polyester Performance Fabric 2.0

PRODUCT: SNT600PC PLUS

FEATURES

- Outstanding colorfastness
- Good water repellency
- Anti-abrasion, anti-mildew

APPLICATIONS

- Suggested for boat covers, car covers and general cover applications.

SPECIFICATIONS	TEST METHOD	
Composition	600D 100% Solution dye polyester	
Weight	380gsm +/- 20gsm	DIN53352
	11oz +/- 0.6oz	ASTM D3776
Color	upon specific request	
Width	1000~2400mm	
Coating	0/1 PU coating	
Hydrostat	≥1000mm	AATCC 127
Water repellency	≥90	AATCC 22
Mildew	99.90%	AATCC 30 Part III
Tensile strength	≥ 1554N/350lbs (Warp) ≥ 1110N/250lbs (Weft)	
Tear strength	≥ 64Nm (Warp) ≥ 64Nm (Weft)	ASTM D1424 Falling-Pendulum (Elmendorf-Type)
UV Colorfastness	≥4.5, fabric face	AATCC 16E, Option 3, 720h
Heat shrinkage	≤2% warp, ≤2% weft	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net
P. 0086-571-28918697
F. 0086-571-28918695

Soyang Haning Factory

No. 36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR., China

Soyang Hangzhou Facotory

No. 1199, Gongyuan Xi Road, Fuyang, Hangzhou City, Zhejiang PR., China

Soyang Europe Ltd

Calder House Metcalf Drive, Altham Accrington, Lancashire BB5 5TU UK

www.soyang.co.uk
P. 0044-161 765 3400
F. 0044-1282 772 982