

## Pure View Coated Backlit Banner



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BW4-610(5028)

### BRIEF DESCRIPTION

- Super strong tenacity for high resolution backlit display
- Matte & gloss surface are both available
- White translucent substrate for long term and large format backlit display, billboard, post board, banner

### FEATURES



### INK PRINTABILITY



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	610 g/sq.m	18 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	550x550 dtex	500x500 denier
Tensile Strength	DIN EN ISO 1421	1890x1500 N/5cm	232x174 lbs/inch
Tear Strength	DIN 53363	345x298 N	80x69 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.