

Premium Tenacity Coated Backlit Banner



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BW4-560(1018)

BRIEF DESCRIPTION

- 1000x1000 18x18 base fabric coated backlit with strong tenacity
- Matte & gloss surface are both available
- White translucent substrate for long term and large format backlit display, billboard, post board, banner

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	560 g/sq.m	16 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	1100x1100 dtex	1000x1000 denier
Tensile Strength	DIN EN ISO 1421	2521x2380 N/5cm	288x272 lbs/inch
Tear Strength	DIN 53363	641x446 N	144x100 lbs
Adhension	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.