







Test Report No.: AJFS2402001659FF Date: MAR.01, 2024 Page 1 of 3

SOYANG TECHNICAL TEXTILE (ZHEJIANG) CO, LTD

NO. 36 JINNIU ROAD, JIANSHAN NEW AREA JIAXING HAINING

Sample Description: PRIME DISPLAY PLUS FABRIC

SGS Ref No.: CZHL2402001146HI

Style No.: ST-1771

The above sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion arising therefrom. Results apply to the sample as received.

Test Requested:

NFPA 701:2023 Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, test method 1.

Test Results: -- See attached sheet --

Conclusion: The tested sample "as received" passes the test method 1 of NFPA 701:2023.

Test Period:

Sample Receiving Date : FEB.23, 2024

Test Performing Date : FEB.23, 2024 TO FEB.29, 2024

Signed for and on behalf of

SGS-CSTC Standards Technical Services Co., Ltd. Anji Branch

Echo Li

Approved Signatory



AJFS2402001659FF Verification: check.sgsonline.com.cn



邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 sgs.china@sgs.com



Test Report No.: AJFS2402001659FF Date: MAR.01, 2024 Page 2 of 3

Test Conducted

The test was conducted in accordance with NFPA 701:2023 Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, test method 1.

Test Specimen

Description	Fabric
Color	White
Area density	227 g/m²
Product configuration	[√] Single Layer, [] Multi-Layer
Size of specimen	400 mm × 150 mm
Exposed surface	Front surface

Conditioning

Cleaning procedure: none

Prior to testing, the specimens were dried in oven at 105 ℃ ±3 ℃ for 30 min.

Test Result

Specimen No.	Mass before test (g)	Mass after test (g)	Mass loss (%)	After flame time (s)	Burn time of fragments or residues (s)
1	14.45	14.38	0.48	0	0
2	14.29	14.19	0.70	0	0
3	14.47	14.34	0.90	0	0
4	14.42	14.31	0.76	0	0
5	14.38	14.24	0.97	0	0
6	14.27	14.13	0.98	0	0
7	14.35	14.26	0.63	0	0
8	14.32	14.18	0.98	0	0
9	14.28	14.12	1.12	0	0
10	14.41	14.27	0.97	0	0
Average	14.36	14.24	0.85	0	0

SD =0.20 3SD =0.60 Mean + 3SD =1.45

SD - Standards deviation





Test Report No.: AJFS2402001659FF Date: MAR.01, 2024 Page 3 of 3

Observations:

Vigorous burning (Yes/No)	Molten droplets or debris (Yes/No)	Odor smoke (Yes/No)
No	Yes	Yes

Performance criteria for test method 1 (Chapter 10)

- 1) Fragments or residues of specimens that fall to the floor of the test chamber shall not continue to burn for more than an average of 2 seconds per specimen for the sample of 10 specimens.
- 2) The average weight loss of the 10 specimens in a sample shall be 40 percent or less.
- 3) No individual specimen's percent mass loss shall deviate more than 3 standard deviations from the mean for the 10 specimens.
- 4) When a retest is required, no individual specimen's percent mass loss in the second set of specimens shall deviate from the mean value by more than 3 standard deviations calculated for the second set.
- 5) When a sample does not demonstrate passing performance in accordance with all of the conditions indicated above, the material shall be recorded as having failed Test Method 1.

Statement: This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

Photo Appendix:



SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307144: or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t(86-572)5018825 f(86-572)5018829 www.sgsgroup.com.cn 中国・浙江・安吉县阳光工业园二区阳光大道301号 邮编:313300 t(86-572)5018825 f(86-572)5018829 sys.china@sgs.com