

**Bubble Free Car Wrapping SAV****PRODUCT: SAV-180G****Description:**

Soft Polymeric PVC film

Color: White

Surface: Glossy

**Release paper:**

Special Embossed PE coated silicone paper, 140g/sq.m 4oz/sq.yd

**Adhesive:**

Solvent polyacrylate, Removable, Grey Color

**MATERIAL DETAILS**

| PROPERTIES   | TEST METHOD            | METRIC   |
|--|------------------------|--|
| Thickness (without protective paper and adhesive)  |                        | 60 micron Polymeric PVC film/2.4mil                                      |
| Adhesive type  |                        | Solvent polyacrylate permanent Transparent                               |
| Dimensional stability  | FINAT TM14             | Adhered to steel, No shrinkage in cross direction, in length 0.50mm max. |
| Temperature resistance   |                        | Adhered to aluminum. -20℃ to +65℃, no variation                          |
| Seawater resistance  | DIN 50021              | Adhered to glass, after 48h/23℃ no variation                             |
| Adhesive power   | FINAT TM1              | After 24h, stainless steel 8-12N/25mm                                    |
| Tensile strength along across  | ASTM D882-02;200MM/MIN | min.26MPa<br>min.25MPa   |
| Elongation at break along across   | ASTM D882-02;200MM/MIN | min 175%<br>min 200%   |
| Shelf life   |                        | Up to 2 years  |
| Application temperature  |                        | Min.+10  |
| Service life by specialist application Under vertical outdoor exposure (normal climate of China) |                        | 5 years  |
| Available Size   |                        | 36"/42"/50"/54"/60" 50m  |

**INK PRINTABILITY**

| Solvent                  | Eco Solvent              | UV                       | Latex                    |
|--------------------------|--------------------------|--------------------------|--------------------------|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Screen Printing          | Dye-Sub Transfer         | Dye-Sub Direct           | Water based              |
|                          |                          |                          |                          |

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Technologies Co., Ltd**  
**(Soyang Headquarter)**West 19th FL, Yongtong Information plaza,  
No. 141 Huancheng Bei Road, Hangzhou  
City, Zhejiang PR., China.[www.soyang.net](http://www.soyang.net)

P. 0086-571-28918690

F. 0086-571-28918695

**Soyang Technical Textile (Zhejiang) Co., Ltd**

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

**Hangzhou Soyang Flexible Material Co., Ltd**

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

**Soyang Europe Ltd**Calder House Metcalf DriveAltham  
Industrial estateAltham Lancashire BB5 5TU  
UK[www.soyang.co.uk](http://www.soyang.co.uk)

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982