





F. 0044 (0) 1282 772982

SUPER CLEAR WINDOW GRAPHIC FILM

PRODUCT: ESCPET-140S

FEATURES / APPLICATIONS:

- 140micron clear PET film with silicone suction layer, adhesive-free, smudge-free and PVC-free, 100% recyclable
- Low-tack, will not leave adverse effect on applying surface, no ghosting will be found even for long time use
- Very easy to cling onto glass, varnished wood, stainless steel, PVC, and other smooth surfaces
- Suitable for Sol/Eco-sol/UV/Latex inks with good image perfomace

MATERIAL DETAILS				
PROPERTIES	TEST METHOD	RESULTS		
Face Film		Clear PET film		
Face Film Thickness		140micron		
Release Liner		50micron matte BOPP		
180°Peel strength (24Hr)		2.5g / 25mm		
Apprearance		clear		
Service temperature		- 40ºC ~ 120ºC		
Storage termperature		10ºC ~ 25ºC		
Storage humidity		30% ~ 60%		
Shelf life		12 months		
Dimensional Stability (300ºF, 48Hr, applied to a		<0.1 inch		
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions		
Availavle Size		1.37x50m/roll		

INK PRINTABILITY

F. 0086-571-28918695

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co.,	Soyang Technical Textile (Zhejiang) Co.,Ltd	Soyang Europe Ltd
Ltd		
(Soyang Headquarters)		
West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.	No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.	Calder House Metcalf Drive Altham Industrial estate Altham Lancashire BB5 5TU UK
www.soyang.net	Hangzhou Soyang Flexible Materials Co., Ltd	www.soyang.co.uk
P. 0086-571-28918690	No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China	P. 0044 (0) 161 765 3400