

Transparent Static Film

PRODUCT: PSF-180T

FEATURES & APPLICATIONS

- 180micron transparent PVC film with 170gsm single side PE-coated paper liner, non-adhesive
- Mostly used for glass, lenses, high-gloss plastic surfaces, and acrylic and other smooth surfaces
- It has obvious effects on product surface production, enhancing product value
- Compatible with Sol/Eco-sol/UV/Latex inks

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Face Film		
Material		Monomer PVC film
Color		Transparent
Thickness	GB/T6672	180 micron
Weight	ISO 4591	230 gsm
Liner		
Material		Copper coated paper
Weight	ISO 4591	170 gsm
Other		
Shrinkage ration		≤0.8%
Width Available		0.914/1.07/1.27/1.52m
Regular Length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918685

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Hangzhou Soyang Flexible Materials Co., Ltd

No.1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982