

Floor Sticker Graphic Film

PRODUCT: FG-1812T

Features& Applications:

- Standblast PVC floor lamination film with transparent adhesive, backed with single side PE-coated paper liner
- Better skid-resistance than other glossy floor lamination film
- Widely used for smooth or semi-smooth floor graphics protection

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Film Material		180±10um monomeric sandblast PVC film
Adhesive type		35±3um transparent permanent adhesive
Release Liner		120±5gsm single side PE-coated white wood-pulp paper
Surface Brightness	D60	7.5
Adhesive Force		1300±200g/inch
Release Force		15±5g/inch
Initial Tack	20Minutes in the standard lab	Ball No.5
Application Temperature		5℃-45℃
Storage Temperature		15℃-40℃
Durability		Outdoor use up to 12 months; Indoor use up to 24 months
Available Width		0.914/1.07/1.27/1.37/1.52m
Regular Length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Technologies Co., Ltd
(Soyang Headquarter)**

West 19th FL, Yongtong Information plaza,
No. 141 Huancheng Bei Road, Hangzhou
City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Hangzhou Soyang Flexible Material Co., Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf DriveAltham
Industrial estateAltham Lancashire BB5 5TU
UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982