



# Floor Sticker Graphic Film

# PRODUCT: FG-4514 Features& Applications:

- Premium quality PVC surface with strong slip-resistance coating, backed with double-side PE-coated paper.
- With PVC surface, it is printable for indoor short time advertising, widely used for any smooth and plane floor surfaces
- Compatible with Solvent, Eco-solvent, UV and Latex inks

#### MATERIAL DETAILS

MATERIAL DETAILS			
PROPERTIES	TEST METHOD	RESULTS	
Film Material		450±10um PVC surface with strong slip-resistance	
Adhesive type		35±3um transparent permanent adhesive	
Release Liner		140gsm double-side PE-coated paper	
Adhesive Force		1200±240g/inch	
Release Force		23±10g/inch	
Initial Tack	20Minutes in the standard lab	≤ Ball No.7	
Application Temperature		10℃-35℃,30%-70% RH	
Storage Temperature		10℃-35℃, 30%-70% RH	
Durability		Indoor use within 3 months	
Available Width		1.07/1.27m	
Regular Length		30m	

### **INK PRINTABILITY**

Solvent	Eco Solvent	uv	Latex
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

# Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

#### www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

#### Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

#### Hangzhou Soyang Flexible Material Co., Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

## **Soyang Europe Ltd**

Calder House Metcalf DriveAltham Industrial estateAltham Lancashire BB5 5TU UK

#### www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982