

STANDARD ONE WAY VISION 1.0

PRODUCT: SUNSHADE-SV64 1.0

Features& Applications:

- 60/40 glossy white/black perforated PVC film, 1 mm holes
- Solvent polyacrylate transparent removable adhesive
- 185 gsm perforated paper + double sides PE coated paper
- Widely used as window graphics, building wraps, retail & commercial signage, POP displays,etc
- Compatible with Sol, Eco-sol, UV and Latex inks with high resolution printing & brilliant image color

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
Film thickness	ISO 4591:1992	180 micron white/black PVC film
Adhesive type		Solvent polyacrylate transparent removable adhesive
Removability		Within 1 year residueless removable from most surfaces
Backing Paper		Perforated paper + Double Sides PE coated paper, 185 g/m ²
Dimensional stability	FINAT TM14	Adhered to glass, 0.2mm in cross direction, in length 1.0mm max.
Temperature resistance		Adhered to glass, -20℃ to +65℃, no variation
Diameter of hole		1.0mm
Perforating Ratio		40%
Seawater resistance	DIN 50021	Adhered to glass, after 48h/23℃ no variation
Adhesive power	FINAT TM 1, after 24h, stainless steel	3~7 N/25 mm
Tensile strength along across	DIN EN ISO 527	min. 15 MPa min. 16 MPa
Elongation at break along across	DIN EN ISO 527	min 120% min 140%
Shelf life		1 year
Application temperature		Min.+10℃
Service life by specialist application Under vertical outdoor exposure (normal climate of China)		1 year
Available Width		0.914/1.07/1.27/1.37/1.52m
Regular Length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huanheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918685

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Hangzhou Soyang Flexible Material Co., Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf DriveAltham Industrial estateAltham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982