

Floor Sticker Graphic Film

PRODUCT: FG-1914

Features& Applications:

- Diagonal pattern clear PVC floor lamination film with transparent adhesive, backed with single-side PE-coated paper
- Better skid-resistance than other glossy floor lamination film
- Widely used for smooth or semi-smooth floor graphics protection

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Film Material		190±10um monomeric diagonal pattern clear PVC film
Adhesive type		48±5um transparent permanent adhesive
Release Liner		140±5gsm single side PE-coated white wood-pulp paper
Surface Brightness	D60	35±5
Adhesive Force		2400±400g/inch
Release Force		15±5g/inch
Initial Tack	20Minutes in the standard lab	Ball No.11
Application Temperature		10℃-35℃, 30%-70% RH
Storage Temperature		10℃-35℃, 30%-70% RH
Available Width		0.914/1.07/1.27/1.37/1.52m
Regular Length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No.
141 Huancheng Bei Road, Hangzhou City,
Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Hangzhou Soyang Flexible Material Co., Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf DriveAltham
Industrial estateAltham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982