



## **Economic Clear SAV 140**

PRODUCT: SAV-120T

Description:

100micron soft clear PVC film with solvent polyacrylate permanent& transparent adhesive

Application:

For short-term outdoor applications such as vehicle wrapping&tri-vision applica-tion. Indoor exposure is almost unlimited.

Compatible inks:

Solvent , Eco-solvent and UV

## MATERIAL DETAILS

MATERIAL DETAILS				
PROPERTIES	TEST METHOD	RESULTS		
Film detail	ISO 4591:1992	100 micron clear PVC film		
Release paper		Single side PE coated silicone paper, 140g/sq.m		
Dimensional stability	under 25°C, ≤ 15days	2.0mm max in cross direction, in length 3.0mm max.		
Adhesive type		Solvent polyacrylate permanent, transparent		
Adhesive thickness		22micron		
Holding power	adherometer	≥ 24H		
Peeling strength(180°)		≥ 8N/25MM		
Shelf life		1 year		
Storage		One year out of direct sunlight at 23 °C and 50% humidity		
Application temperature		Min.+10 ℃		
Available width		0.914/1.07/1.27/1.37/1.52m		
Regular length		50m		

## INK PRINTABILITY

Solvent	Eco Solvent	uv	Latex
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd	Soyang Technical Textile (zhejiang) Co.,Ltd	Soyang Europe Ltd
(Soyang Headquarter)		
West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.	No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.	Calder House Metcalf DriveAltham Industrial estateAltham Lancashire BB5 5TU UK
www.soyang.net	Hangzhou Soyang Flexible Material Co.,Ltd	www.soyang.co.uk
P. 0086-571-28918685		P. 0044 (0) 161 765 3400
F. 0086-571-28918695	No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China	F. 0044 (0) 1282 772982