

450gsm Knitted Semi-coating Frontlit



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

AW2-450(1012)

BRIEF DESCRIPTION

- White substrate for high quality frontlit displays
- Super strong & durable with textured softness
- Excellent for long term outdoor billboards, banners

FEATURES



HIGH TENACITY



FIRE-RESISTANT



SUPER WIDE

INK PRINTABILITY



SOL



ECO SOL



UV



LATEX



SCREEN Printing

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	450g/sq.m	13.2oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	1100x1100 dtex	1000x1000 denier
Tensile Strength	DIN EN ISO 1421	1600x1320N/5cm	179x148 lbs/inch
Tear Strength	DIN 53363	300x261 N	67x59 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.