

Soft Tent

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-322UT

BRIEF DESCRIPTION

- 100% polyester fabric with 500D x 500D woven base
- Good tensile, tear strength & water resistance feature
- Can be used as short-time promotion tent, parasol, etc

FEATURES



PVC-FREE



PHTHALATE FREE



WATER-PROOF

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	190 g/sq.m	5.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	550x550 dtex	500x500denier
Weave Method	N/A	Woven	
Shrinkage	ISO 9866-2-1991	≤3%	
Tensile Strength	DIN EN ISO 1421	2024x1110 N/5cm	231x127 lbs/inch
Tear Strength	DIN53363	251x189 N	56x43 lbs
Flame Resistance	SGS	B1	
Recommend Fixation Temperature	N/A	190°C,30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.