

# Heavy Mesh

## Mesh-914



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

### BRIEF DESCRIPTION

- 100% polyester warp-knitted mesh with very good strength
- 37% air-flow through
- A PVC backing is available which prevents ink spray through when printing
- Widely used for wall wrap, fence, backdrops, hanging display, theatrical, large format advertisement, etc.

### FEATURES



### INK PRINTABILITY



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	330g/sq.m	10oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	1100x1100dtex	1000x1000denier
Tensile Strength	DIN EN ISO 1421	1460x2006 N/5cm	167x230 lbs/inch
Tear Strength	DIN 53363	403x382 N	91x86 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701	DIN 4102-1-B1, NFPA 701	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

