

Premium Mesh With Liner

Mesh-12V

Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester warp-knitted mesh
- 44% air -flow through
- Coming with a PVC backing which makes the feeding and printing much easier
- Widely used for wall wrap, fence, hanging display, etc.

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	350g/sq.m	10.5oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	1100x1100dtex	1000x1000denier
Tensile Strength	DIN EN ISO 1421	1250x1250 N/5cm	140x140 lbs/inch
Tear Strength	DIN 53363	300x310N	67x70lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701	DIN 4102-1-B1, NFPA 701	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.