

Standard Mesh

Mesh-1812



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester warp-knitted mesh
- 35.8% air-flow through
- A PVC backing is available which prevents ink spray through when printing
- Widely used for wall wrap, fence, backdrops, hanging display, theatrical, large format advertisement, etc.

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	250g/sq.m	7.5oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	550x1100dtex	500x1000denier
Tensile Strength	DIN EN ISO 1421	1100x1200 N/5cm	126x137 lbs/inch
Tear Strength	DIN 53363	210x220N	47x50 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701	DIN 4102-1-B1, NFPA 701	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

