

# **Lux Banner Flag**

ST-1102T/ST-1102D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

### **BRIEF DESCRIPTION**

- 100% polyester fabric, high glossy surface brings brilliant colors
- Heavy satin style with good opacity, popularly used as luxury satin flag, sewing flag, indoor banner, etc
- Soft hand feel, good wrinkle resistance, can recover quickly after folded

# **FEATURES**









#### **INK PRINTABILITY**





## **MATERIAL DETAILS**

		IMPERIAL
DIN EN ISO 2286-2, ASTM D751	200 g/sq.m	5.9 oz/sq.yd
DIN 60001, ASTM D7641	100%polyester	
N/A	Warp-knitted	
ISO 9866-2-1991	≤2%	
ANSI PH2.19, ISO 5/2	(59±4)%	
DIN EN ISO 1421	280x1646 N/5cm	32x188 lbs/inch
DIN53363	77x235 N	17x53 lbs
DIN 4102-1-B1, NFPA 701 Test1,	DIN 4102-1-B1, NFPA 701 Test1,	
N/A	190°C, 30s	
DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
DIN EN ISO 3759, ASTM D751-2006	50m	55yds
C	DIN 60001, ASTM D7641  N/A  ISO 9866-2-1991  ANSI PH2.19, ISO 5/2  DIN EN ISO 1421  DIN53363  DIN 4102-1-B1, NFPA 701 Test1,  N/A  DIN EN ISO 3759, ASTM D751-2006	DIN 60001, ASTM D7641       100%pol         N/A       Warp-k         ISO 9866-2-1991       ≤29         ANSI PH2.19, ISO 5/2       (59±4         DIN EN ISO 1421       280x1646 N/5cm         DIN53363       77x235 N         DIN 4102-1-B1, NFPA 701 Test1,       DIN 4102-1-B1, I         N/A       190°C         DIN EN ISO 3759, ASTM D751-2006       Max 320cm         DIN EN ISO 3759, ASTM D751-2006       50m

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







