

Modern Flag Pro

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-1201T/ST-1201D

BRIEF DESCRIPTION

- 100% polyester warp-knitted fabric with special mesh structure
- Ultra soft hand feel, very good strength for indoor and outdoor use
- With a certain ventilation rate for extend lifespan
- Very good antistatic property for high stable & flawless printing.

FEATURES



PVC-FREE



PHTHALATE FREE



SOFT HANDFEEL



EXCELLENT INK PENETRATION

INK PRINTABILITY



DYE direct



DYE paper



SCREEN Printing

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	110 g/sq.m	3.2 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	ISO 9866-2-1991	≤2%	
Tensile Strength	DIN EN ISO 1421	319x497 N/5cm	36x57 lbs/inch
Tear Strength	DIN53363	73x95 N	16x21 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommended Fixation Temperature	N/A	190℃, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	100m	110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.