





Test Report No.: AJFS2408009492FF Date: AUG.29, 2024 Page 1 of 6

SOYANG TECHNICAL TEXTILE (ZHEJIANG) CO, LTD

NO. 36 JINNIU ROAD, JIANSHAN NEW AREA JIAXING HAINING

Sample Description: NIGHTSTAR BLACKBACK HYPER

SGS Ref No.: CZHL2408006356HI

Style No.: ST-216H

The above sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion arising therefrom. Results apply to the sample as received.

Test Requested:

DIN 4102-1:1998-05 Fire behaviour of building materials and building components, Part 1: Classification of building materials, Requirements and testing, Class B1 materials---For all materials except flooring.

Test Results: -- See attached sheet -

Classification: The tested sample meets class B1 materials requirements of DIN 4102-1:1998-05.

Test Period:

Sample Receiving Date : AUG.12, 2024

Test Performing Date : AUG.12, 2024 TO AUG.27, 2024

Signed for and on behalf of

SGS-CSTC Standards Technical Services Co., Ltd. Anji Branch

Echo Li

Approved Signatory





Test Report No.: AJFS2408009492FF Date: AUG.29, 2024 Page 2 of 6

I. Test conducted

This test was conducted as per DIN 4102-15:1990 Fire behaviour of building materials and building components – 'Brandschacht' apparatus, DIN 4102-16:2021 Fire behaviour of building materials and building components– 'Brandschacht' tests and DIN 4102-1:1998-05 Clause 6.2.5, and Classification according to DIN 4102-1:1998-05 Clause 6.1 Class B1 materials.

II. Sample details

General description	Nightstar Blackback Hyper (provided by client)
Color	Black
Area Density	254 g/m ²
Size of sample	190mm×1000mm & 190mm×90mm & 230mm×90mm
Exposed (tested) surface	Black surface

Conditioning

Prior to testing, the sample was conditioned at least 14 days to constant mass at a temperature of 23 ± 2 °C, and a relative humidity of 50 ± 5 %.

III. Test results

1) "Brandschacht" Test according to DIN 4102-15 &16

Results of "Brandschacht" Test (part 1)								
Line		Unit	Test direction					
No.		Offic	Lengthwise	Widthwise				
1	Specimen fixings according to DIN 4102 part 15, table	/	1	/				
2	Max. flame height above lower sample edge;	cm	30	50				
3	Time 1)	min:s	00:20	00:22				
	Melting/burning through		Yes	Yes				
4	Time 1)	min:s	00:02	00:02				
	Back of specimen		Yes	Yes				
5	Flaming/glowing, Time 1)	min:s	00:02	00:02				
6	Discolouring, Time 1)	min:s	00:01	00:01				
	Burning droplets		Yes	Yes				
7	Begin 1)	min:s	00:05	00:06				
	Amount		/	/				
8	Specimen material falling off in separate droplets		\checkmark	\checkmark				
9	Specimen material falling off continuously		/	/				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, Indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, **Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



Test Report No.: AJFS2408009492FF Date: AUG.29, 2024 Page 3 of 6

	Results of "Brandschad	cht" Test	(part 2)			
Line		Unit	Test direction			
No.		Unit	Lengthwise	Widthwise		
	Burning parts		No	No		
10	Begin 1)	min:s	/	/		
11	Parts of sample falling off separately		/	/		
12	Parts of sample falling off continuously		/	/		
13	Duration of continued combustion on mesh base (max.)	min:s	No	No		
	Burner flame impairment by dripping/falling material		No	No		
14	Time 1)	min:s	/	/		
	Premature ending of test		/	/		
15	End of burning at specimen 1)	min:s	/	/		
16	Time when test terminated (if applicable) 1)		/	/		
	Burning after end of test		No	No		
17	Duration	min:s	/	/		
18	Number of specimens		/	/		
19	Front of specimen		/	/		
20	Back of specimen		/	/		
21	Height of flame	cm	/	/		
	Glowing after end of test		No	No		
22	Duration	min:s	/	/		
23	Number of specimens		/	/		
24	Front of specimen		/	/		
25	Back of specimen		/	/		
26	Top half of specimen		/	/		
27	Bottom half of specimen		/	/		
	Smoke density		Yes	Yes		
28	≤ 400 %×min		\checkmark	√		
29	> 400 %×min		/	/		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized atteration, foregry or falsification of the content or appearance of this document is unival and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CAI,Doccheck@sgs.com"

or email: CN.Doccheck@sgs.com No.301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgsgroup.com.cn 中国・浙江・安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 sgs.china@sgs.com



Test Report No.: AJFS2408009492FF Date: AUG.29, 2024 Page 4 of 6

Results of "Brandschacht" Test (part 3)									
Line		Lloit	Test direction						
No.		Unit	Lengt	hwise	Widthwise				
	Residual length		,	1	/				
30	Single results	cm	70	71	56	58			
30 Single results	Offigie results		70	70	58	57			
31	Average of the single results	cm	70.2		57.3				
	Smoke temperature		/		/				
32	Max. of average	$^{\circ}$	123		118				
33	Time 1)	min:s	02:	46	02:32				

Note: 1) time from start of testing

Class B1 materials:

If the residual length measured after the first test is 45cm or greater, further tests are not required.

2) Ignitibility test according to DIN 4102-1 Clause 6.2.5

a) Surface ignition

Fire application time: 15s

Parameter		Le	engthwi	se		Widthwise				
	1	2	3	4	5	6	7	8	9	10
Whether or not flaming extinguished before reach the gauge mark (Yes/No)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Whether or not flaming reach the measuring mark within 20 seconds (Yes/No)	No	No	No	No	No	No	No	No	No	No
Time for the flame tip to reach the gauge mark (s)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Afterflame time (s)	10	11	3	8	6	21	19	6	17	12
Max. flame height (cm)	5	7	7	6	5	7	6	4	7	5
Molten dripping (Yes/No)	No	No	No	No	No	No	No	No	No	No
Smoke developments (visual impression)	Small				Small					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Altention is drawn to the limitation of liability indemnification and jurisdiction issues defined therein. Any holder of this document is advised that inmation contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's soler responsibility is to its Client and this document does not exonerate perfuse to a transaction from exorating all their rights and obligation under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlauf and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com"

^{*}Reduction in number of test (DIN 4102 Part 16, clause 5.2)



Test Report No.: AJFS2408009492FF Date: AUG.29, 2024 Page 5 of 6

b) Edge ignition

Fire application time: 15s

Parameter		Le	engthwi	se		Widthwise				
	1	2	3	4	5	6	7	8	9	10
Whether or not flaming extinguished before reach the gauge mark (Yes/No)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Whether or not flaming reach the measuring mark within 20 seconds (Yes/No)	No	No	No	No	No	No	No	No	No	No
Time for the flame tip to reach the gauge mark (s)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Afterflame time (s)	0	0	0	0	0	0	0	0	0	0
Max. flame height (cm)	4	6	6	5	4	7	6	6	7	5
Molten dripping (Yes/No)	No	No	No	No	No	No	No	No	No	No
Smoke developments (visual impression)	Small				Small					

Note: NA = Not applicable

IV. DIN 4102-1:1998 Criteria for classification

- 1) All materials, except flooring, may be classed as **B1** materials if they meet the following requirements a) and b):
- a) The test using the 'Brandschacht' apparatus described in DIN 4102-15 (cf. subclause 6.1.3.1) shall be deemed passed if
- The mean value for the residual length (portion of specimen that has not burned or charred; cf. subclause
- 9.1 of DIN 4102-16) of each specimen is at least 15 cm and no individual values are lower than 0 cm,
- The mean effluent temperature does not exceed 200 °C in any test,
- The requirement for the residual length of each specimen is met even where there is afterflame, afterglow, or smouldering.
- b) Pass DIN 4102-1:1998 sub-clause 6.2.5 Ignitability Test if

For each specimen, flaming doesn't reach the gage mark within 20s after flame application.

2) Materials may be classed as **B2** materials if they pass the ignitibility test specified in DIN 4102-1:1998 subclause 6.2.5.

For each specimen, flaming doesn't reach the gage mark (150mm marks) within 20s after flame application.

3) Combustible materials which cannot be classed as B1 or B2 materials shall be classed as B3 materials.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleat available on request or accessible at https://www.sg.com/en/Terms-and-Conditions. Attention faramy to the limitation of liability indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflect the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sol responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligation under the transaction focuments. This document cannot be reproduced except in full, without prior time approval of the Company. An unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecute to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and suc sample(s) are retained for 30 days only.



Test Report No.: AJFS2408009492FF Date: AUG.29, 2024 Page 6 of 6

STATEMENTS:

This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

This test report does not replace any mandatory certification of the product that may be required.

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire and smoke hazard of the product in use.

Photo Appendix:



SGS authenticate the photo on original report only

*** End of Report ***

