

Sahara Soft Backlit

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-1003T/D

BRIEF DESCRIPTION

- 100% polyester woven fabric with an extra dense structure
- Super smooth surface, truly soft & delicate to the touch
- Outstanding crease-free ability, ensuring ease of handling and transportation
- High printing stability with vivid colors, suitable for inline fixation
- 5-meter ultra-wide, impressive as high-end backlit material for wideformat application

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	180 g/sq.m	5.3 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	ISO 9866-2-1991	≤3%	
Light Transmittance	ANSI PH2.19, ISO 5/2	40%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.