Starlight Premium Hyper

ST-601UTH

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester woven coated fabric with a dense structure
- Improved soft hand feel with excellent wrinkle resistance
- Perfect for UV printing, also compatible with Latex and dye paper transfer
- Truly good light transmittance for bright &uniform illumination, ideal used as backlit fabric
- DBDPE-FREE, fully REACH compliant for environmental safety

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	175 g/sq.m	5.1 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	ISO 9866-2-1991	⩽3%	
Light Transmittance	ANSI PH2.19, ISO 5/2	(40±5)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	PD-3200RXD-260	190℃-200℃, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

SOYANG
www.soyang.net

ISO 9001

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

Global Recycled Standard